

## PRIMEGUARD PRIMER



### Description:

PrimeGuard is a formulation of petroleum based waxes, plasticizers, and moisture displacing corrosion inhibiting compounds. PrimeGuard will not dry out, harden or crack and is applicable for dry or wet surfaces. PrimeGuard conditions the metal structure by displacing any surface moisture. This provides SCC Wax Wraps with a surface that allows it to protect the metal structure to its fullest potential. PrimeGuard is offered in above and belowground grades.

### SPECIFICATIONS:

Color	Brown,White
Coverage	1 gal/100 ft <sup>2</sup>
Flash Point	507°F
Drop Melt Point	176°F
Operating Temp	-50°F - 155°F
Application Temp	0°F +

## PRIMEGUARD 250



### Description:

PrimeGuard 250 is a formulation of petroleum based waxes, plasticizers, and moisture displacing corrosion inhibiting compounds. PrimeGuard 250 is a Non-Melting primer designed to be used as a surface conditioner for above and belowground applications with high ambient temperatures and hot surfaces.

PrimeGuard 250 will not dryout, harden, melt, or crack.

### SPECIFICATIONS:

Color	Brown
Coverage	1 gal/100 ft <sup>2</sup>
Flash Point	507°F
Drop Melt Point	300°F
Operating Temp	-50°F - 250°F
Application Temp	0°F+

Packaging: 4-1 gallon pails/case